PCB Copper

HITACHI Inspire the Next

CMI165[®] Unique temperature-

Unique temperature-compensated surface and trace copper thickness

Find out more

These gauges are a great complement to our XRF coatings analysers. To place your order contact contact@hitachi-hightech-as.com

MORE INFORMATION

To find out more about the CMI95M® or our range of PCB gauges, visit

www.hitachi-hightech.com/hha



ACCURATE IN-PROCESS INSPECTION RESULTS REGARDLESS OF COPPER TEMPERATURE

Temperature can affect the measurement on a copper sample. Our CMI165[®] can compensate for the temperature to produce accurate in-process inspection results regardless of the tempature of the copper. It is an ideal gauge for quality assurance and inspection for:

- PCM manufacturing and assembly.
- Copper surface thickness.

Our CMI165[®] gauge is versatile and portable. It comes equipped with a protective case and its durable design can be taken into the harshest environments. The CMI165[®] is a good choice to:

- Measure Cu on hot or cold PCBs.
- Reduce waste by eliminating the need for coupons.
- Measure Cu thickness on foils or laminates in $\mu\text{m},$ mils or oz.
- Sort Cu by weight at incoming inspection, prior to drilling, shearing or plating.
- Quantify Cu thickness after etching or planarizing.
- Verify Cu plating thickness on PCB surfaces.
- Measure thin etched traces down to 204 μm without use of standards.

KEY FEATURES:

- Temperature compensation
- Durable design.
- Proprietary SRP-T1 replaceable probe.
- Illuminated probe tip for easy positioning.
- User interface in English or Simplified Chinese.

RELIABLE NON-DESTRUCTIVE ANALYSIS REGARDLESS OF Cu TEMPERATURE



PROPRIETARY SRP-T1 MEASUREMENT PROBE

Replaceable Probe Tip - no recalibration necessary.

Ensures no factory downtime.

SPECIFICATIONS

- 4-point electrical probe with resistance method to ensure compliancence with EN 14571.
- High repeatabilty and reliability.
- Statistical analysis includes data recording, average, standard deviation and high-low reporting.
- Factory calibrated and certified.
- Customisable for specific applications.
- Static or continuous mode measurement.
- Powered by AA batteries.

PCB GAUGE COMPARISON CHART

We offer multiple choices for a PCB gauge within the PCB industry to provide you with the best and most cost-effective solution available for your application needs. Please reference the comparison chart below or contact us at **contact@hitachi-hightech-as.com** for our expert advice.

	CMI95M	CMI165	CMI511	CMI563	CMI760
Technique	Microresistance	Microresistance	Eddy	Microresistance	Microresistance
Copper Foil	•	•		•	•
Copper Laminate	•	•		•	•
Copper – Surface		•		٠	٠
Copper – Fine Line		٠		٠	٠
Copper Thru-hole			•		Optional
Temperature Compensation		•	•		ETP Probe
Replacement Probe Tip	N/A	•		•	SRP-4 Probe
Unit Selection	oz or µm	mil or µm	mil or µm	mil or µm	mil or µm
Copper Thickness Range					
μm	8 indicator lights: 5 – 140	Electroless: 0.25 – 12.7 Electroplated: 2 – 254	2 - 102	Electroless: 0.25 – 12.7 Electroplated: 0.25-152	Surface: 0.25 – 254 Thru-hole: 1 – 10
mil		Electroless: 0.01 – 0.5 Electroplated: 0.1 – 10	0.08 - 4	Electroless: 0.01 – 0.5 Electroplated: 0.01 – 6	Surface: 0.01 – 10 Thru-hole: 0.08 – 4

Our global network of service hubs offer a full range of technical support to keep you up and running. We are A2LA certified* for coating thickness calibrations and standards which means that your CMI165[®] will be ISO complaint. *A2LA accreditation is applicable to work performed by Hitachi High-Tech Analytical Science America, Inc.



If you'd like to learn more about CMI165[®] gauge visit www.hitachi-hightech.com/hha or email one of our experts at contact@hitachi-hightech-as.com to book a demo.

@Hitachi High-Tech Analytical Science

This publication is the copyright of Hitachi High-Tech Analytical Science and provides outline information only, which (unless agreed by the company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or regarded as the representation relating to the products or services concerned. Hitachi High-Tech Analytical Science's policy is one of continued improvement. The company reserves the right to alter, without notice the specification, design or conditions of supply of any product or service.

Hitachi High-Tech Analytical Science acknowledges all trademarks and registrations.

© Hitachi High-Tech Analytical Science, 2017. All rights reserved.

Part number: OIIA/165B/0413

